



These window shades/ sunscreens are a popular stylish window covering. They are partially transparent, softening harsh sunlight and UV. At the same time they allow an outside view from indoors, but not the other way around.

- Great vistas enjoyed while privacy is maintained
- Furnishings and floor coverings preserved in their fresh condition and rich colours

Chic designer colours and textures to match a wide range of decor

Our blinds can cater for classic or contemporary, subtle or bold, in light or dark colours, to work with any space.

Avoiding the need for artificial light – saving power

These blinds can let enough light in without people having to squint in the brightness. This can make artificial lighting unnecessary, saving on power bills.

Easy smooth operation with optional motorisation

Blinds are easy to open, close, and adjust. Optional motorization with remote control is also offered utilising efficient JAI products. Blinds can be stopped at exact position required.

Specifications

Size

- Minimum width: 400mm
- Maximum width: 3,000mm (wider available upon request)
- Maximum drop: 2,700mm (longer available upon request)
- Sill depth required for inside (reveal) mount:
 - For 38mm tube: 63mm with max drop of fabric
 - For 45mm tube: 70mm with max drop of fabric
- Linking (side by side):
 - Max for 2 linked blinds: 5,000mm width x 2,500mm drop
 - Max for 3 linked blinds: 7,500mm width x 2,500mm drop
- Chain:
 - Standard size is two thirds of drop but any length is available on request
 - Plastic, stainless, and steel continuous loop sizes – 700mm, 1,000mm, 1,200mm, 1,400mm, 1,600mm, 2,000mm

Components

- Fabric:
 - Woven: 73% PVC and 27% Polyester, openness: 5%
 - Hard wearing and dirt-resistant
 - Insulation properties: up to 20% with energy savings up to 33%
 - UV rating: 90-96% blocking
 - Fire retardant: USA / NFPA 701 small and large
 - Shaw
- Chain:
 - Continuous loop (no joiner)
 - Colours: black, white, ivory, grey, silver, or stainless steel
- Base rail:
 - Shapes: round, oval, or flat
 - Colour options: anodised, black, pearl bronze, grey, ivory, and white

- Top rail:
 - Heavy duty 38mm Aluminium top rail for blinds up to 4m² area
 - Extra strength 45mm top rail for blinds over 4m²
 - Blinds over 3m wide require ultra strength top rail at special price - available upon request
 - Retractable pin: allows for easy fitting and gives approx 2mm comfort factor when fitting blinds
- Spring Assist: used in blinds over 4m² in area to ease lifting
- Brackets: colour: white, ivory, black, or grey

Installation

- Installation items included: brackets, screws, safety chain holder, chain stops, and child safety components
- Easy to lift, angle, fit, and install with simple instructions provided

Operation


- Chain controls: choice of left or right hand side
- Roll direction:
 - Back-rolled standard for outside mounted blinds to keep fabric close to window;
 - Front-rolled standard for inside mount to avoid obstruction of knobs, handles, and winders

Cleaning

- Remove dust with vacuum cleaner or compressed air
- Clean with sponge or soft brush dipped in soapy water, then rinse with clean water, and leave blind down until completely dry
- Do not scrub, use solvents or any abrasive substance that might damage the coating of the fabric.

Colour range

A complete range of Shaw fabrics are available. Colour samples are available on request.



For more information please phone:

0800 222 036

Order line fax

0800 222 037